

				СПЕЦИФИКАЦИЯ								
				Поз.	Обозначение	Наименование		Кол.	Масса ед., кг	примеч.		
						Армирование ребер						
				1	ГОСТ 5781–82	Ø20 А–III	L=5500	42	13.59	570.78		
				2	ГОСТ 5781–82	Ø20 А–III	L=5600	84	13.83	1161.72		
				3	ГОСТ 5781–82	Ø20 А–III	L=4000	12	9.88	118.56		
				4	ГОСТ 5781–82	Ø20 А–III	L=4100	24	10.13	243.12		
				5	ГОСТ 5781–82	Ø25 А–III	L=7000	12	26.95	323.4		
				6	ГОСТ 5781–82	Ø25 А–III	L=7100	24	27.34	656.16		
				7	ГОСТ 5781–82	Ø16 А–III	L=2500	8	3.95	31.6		
				8	ГОСТ 5781–82	Ø16 А–III	L=2600	16	4.11	65.76		
						Нижняя зона вдоль буквенных осей						
				9	ГОСТ 5781–82	Ø16 А–III	L=5800	289	9.16	2647.24		
				10	ГОСТ 5781–82	Ø16 А–III	L=3000	82	4.74	388.68		
				11	ГОСТ 5781–82	Ø16 А–III	L=2800	175	4.42	773.5		
				12	ГОСТ 5781–82	Ø25 А–III	L=5800	4	22.33	89.32		
						Нижняя зона вдоль цифровых осей						
				13	ГОСТ 5781–82	Ø16 А–III	L=4300	120	6.79	814.8		
				14	ГОСТ 5781–82	Ø16 А–III	L=2250	64	3.56	227.84		
				15	ГОСТ 5781–82	Ø12 А–III	L=5170	27	4.6	124.2		
				16	ГОСТ 5781–82	Ø16 А–III	L=3750	48	5.93	284.64		
				17	ГОСТ 5781–82	Ø16 А–III	L=7300	93	11.53	1072.29		
				18	ГОСТ 5781–82	Ø16 А–III	L=3000	48	4.74	227.52		
				19	ГОСТ 5781–82	Ø16 А–III	L=5800	93	9.16	851.88		
						Верхняя зона вдоль буквенных осей						
				20	ГОСТ 5781–82	Ø16 А–III	м	2262	1.58	3573.96		
				21	ГОСТ 5781–82	Ø20 А–III	L=2390	24	5.9	141.6		
				22	ГОСТ 5781–82	Ø20 А–III	L=1490	24	3.68	88.32		
				23	ГОСТ 5781–82	Ø16 А–III	L=8390	3	13.26	39.78		
				24	ГОСТ 5781–82	Ø20 А–III	L=4000	66	9.88	652.08		
				25	ГОСТ 5781–82	Ø20 А–III	L=3000	24	7.41	177.84		
				26	ГОСТ 5781–82	Ø10 А–I	м	547	0.62	339.14		
				27	ГОСТ 5781–82	Ø10 А–I	м	143	0.62	88.66		
				28	ГОСТ 5781–82	Ø16 А–III	L=2390	79	3.78	298.62		
				29	ГОСТ 5781–82	Ø16 А–III	L=4000	204	6.32	1289.28		